

# MP10U H.265 UVC HDMI Media Player



**H.265 UVC HDMI Media Player** – complete with video encoder and decoder functions, is a versatile professional audio and video decoding device. It is capable of supporting H.265/H.264 IP Stream inputs, playing video files from a USB drive, and outputting them to HDMI and USB (UVC to computer). In addition, it can also encode videos from the USB drive into various streaming formats, such as RTMP/RTMPS, HTTP, RTSP, SRT, UDP, RTP, etc. This multi-functional device provides a comprehensive solution for your audio and video needs.

With high integration and cost-effective design, this device widely used in variety of fields, such as Multimedia Distribution, Advertisement Display, Digital Signage, CCTV, Long Distance Video transmit (with our encoder), etc.

## Product features

1. Embedded Linux System, stable and effective, 7 x 24h working time.
2. Friendly Web Control UI, default IP is 192.168.1.169 (as Decoder), 192.168.1.168 (as Encoder).
3. Support output resolution - 1080P/1080I/720P@60FPS, etc.
4. USB Input: play videos from a USB drive.
5. USB Output: UVC to computer (output video to computer through USB)
6. Support Text and image insert as OSD output.
7. With English control panel & language customizable.
8. Support H.265/H.264 baseline /main /high profile decoding.
9. Support firmware upgrade.
10. Support remote control via router port forward.

## Application

1. Long distance video transfer.
2. Internet TV (IPTV) HD capture system
3. Internet video conference front-end capture
4. Digital signage HD streaming server
5. Teaching broadcast
6. Network monitoring system platform front-end capture

**Specification:**

<b>Input</b>	TS Protocols	SRT / HTTP(S) / FLV / RTSP / RTMP(S) / UDP/RTP (Unicast/Multicast), ONVIF, etc.
	Private	HTTP PTE/PTL
	U-disk (FAT32/NTFS)	H264 video files by our transcode-tool.exe, max supports 1080p@60
	Audio	3.5MM Line-in
<b>Video Decoding</b>	Video type	H.265 main profile H.264 baseline/main/high profile L4.2 MJPEG/JPEG baseline
	FPS	1-60fps for 1080P and below, 4K@30fps
	bitrate (kbps)	32-32000
	Resolution	Max 3840*2160@30fps / 1080P@60fps
<b>Audio Decoding</b>	Type	G711A/G711U/AAC/AAC+/AAC++/AC3/MP2/MP3
	Audio Channels	L/R Stereo
	Sample rates	8000/11250/22500/44100/48000 Hz
<b>Video output</b>	HDMI & UVC	1080P@60/1080P@50/1080P30/1080P25/720P60/720P50/576P50/480P60
	CSC	Brightness, Contrast, Hue, Saturation
<b>Audio output</b>	HDMI	48KHz L / R
	3.5MM	L / R
<b>Others</b>	Ethernet Ports	1000 Mbit/s full-duplex
	admin page	HTTP WEB
	Power	12V 1A <5W
	Operating temperature	-20°C + 80°C
	Relative Humidity	5% to 90% non-condensing
	Dimension (Lx Wx H)	85 X 55 X 30mm
	Weight	130g

**Our Services**

1. 1-Year Warranty.
2. Online, remote help.
3. Encoder Function customizes.
4. OEM & ODM welcomed.